

NAOMI - ALL IN ONE TEXTILE

Tecnical bulletin

BLACK BACK

ITEM	DESCRIPTION	NORM	UNIT	VALUE
PRODUCT	Article Code			SN-BB260
	Composition	DIN 60001	%	100% PCT POLYESTER
	Weight (fabric+coating)	DIN EN ISO 2286-2	gr/m <sup>2</sup>	FABRIC 150 + PU BLACK 110
	Colour			WHITE (face out), BLACK (face in)
	Finishing			MATT
	Thickness	ASTM D-1777	mm	0,52
	Working temperature		°C	180±200
	Available Sizes			1,60-3,20*50m
	Weaving			WARP KNITTED
	Fire reaction	DIN -4102	CLASS	B1
BASE FABRIC TECHNICAL CHARACTERISTICS	Warp Yarn Count + Type	DIN EN ISO 2060	Dtex	83
	Weft Yarn Count + Type	DIN EN ISO 2060	Dtex	83
	Threads Warp	ASTM D-3887 SEZ. 12	n°	12,6
	Threads Weft	ASTM D-3887 SEZ. 12	n°	18
	Warp Tensile Strength	ISO 13934,1-2003	N	700
	Weft Tensile Strength	ISO 13934,1-2003	N	430
	Warp Elongation	ISO 13934,1-2003	%	100
	Weft Elongation	ISO 13934,1-2003	%	77
	Tearing Strength Warp	ISO 13937.2-2000	N	36
	Tearing Strength Weft	ISO 13937.2-2001	N	27
	Bursting Strength	ASTM D 3787-2007	N	769

PRODUCT DESCRIPTION	<p>What's Naomi? It's a fabric made from monoaxial polyester fibers. PCT* has been adopted (instead of the usual PET) because is an innovative resin, always belonging to the polyester family, but with superior characteristics: +18°C heat resistance and +20% tear resistance. PCT therefore allows the use of higher temperatures in the sublimation phase.</p> <p>* PCT: Polycyclohexylenedimethylene terephthalate, CAS number: 25135-20-0</p>
APPLICATIONS	<p>The product is self-extinguishing in class B1 (DIN 4102-B1), therefore designed for indoor communications, especially in large public gatherings such as theatres, trade fairs and airports and outdoors (for applications not exceeding 12 months). Ideal for structures, frames and pop-ups that require a block-out effect.</p>
PRINTABILITY	<p>For sublimation: direct and indirect. For ink-jet: latex and UV inks. For screen printing: with all inks of the series.</p>
STORAGE PERIOD	<p>24 months under ordinary condition at the temperature mean of 22 °C (min. 12 °C, max. 32 °C) and relative humidity of 45 - 65%. The material must stay in its box and does not have to be at sun light, otherwise the coating can be damaged.</p>
REACH NORMS	<p>REACH - Complying with the Italian Decree-Law n. 133 issued on 14.09.2009 published on the Italian Gazzetta Ufficiale, we inform that no SVHC are present in a concentration exceeding 0,1% in the base fabric nor in the coating. For further information, please ask for the updated regulation of SVHC taken into consideration by REACH (Registration Evaluation Authorization of Chemicals).</p>
NOTES	<p><i>Published information is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of the products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to changes without prior notice.</i></p>