

1352**Description**

This double-sided tape consists of a polyester film carrier which is layered on both sides with different adhesives. The adhesive on the covered side of the tape has excellent permanent adhesive qualities. The adhesive on the open side allows easy removal from many surfaces. The adhesive is lined with a double sided siliconised paper.

Carrier

Polyester film, 23 micron

Liner

Siliconised paper, white, 90 g/m²

Adhesive

Covered side: rubber; open side: modified dispersion acrylate

Area of use

This tape is especially suitable for the installation of carpets at conferences or exhibitions (with high cohesion and easy removal). Not appropriate for porous stone or marble.

Technical data

Thickness* (adhesive + carrier)	190 micron
Temperature resistance***	-40°C to + 70°C
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	Covered side: after 1 min: 40 N/25mm after 20 min: 40 N/25mm after 24 h: 42 N/25mm Open side: after 1 min: 4 N/25mm after 20 min: 5 N/25mm after 24 h: 7 N/25mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	Covered side: at 23°C >240 h Open side: at 23°C >120 h
Shelf life**	1 year
Application temperature	> + 18°C

* average

** in original packaging, at 20°C and 50% relative humidity

*** normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

