

Description

This double-sided tape consists of a cloth carrier, layered on both sides with modified dispersion acrylate adhesives. The adhesives are plasticiser resistant. The adhesive on the covered side of the tape has permanent adhesive qualities. The adhesive on the open side allows easy, residueless removal from many surfaces. The adhesive is lined with a white double-sided silicone paper.

Carrier

Rayon

Liner

Silicone coated paper on both sides, 90 g/m², white

Adhesive

Modified dispersion acrylate

Area of use

This tape is especially suitable for the installation of temporary carpets at conferences or exhibitions (with high adhesion and easy removal). Also suitable for PVC floor surfaces and carpets with a back layer of PVC.

Technical data

Thickness* (adhesive + carrier)	290 micron		
Temperature resistance***	-20°C to +100°C		
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)		covered side	open side
	after 1 min	13 N/25mm	7 N/25mm
	after 20 min	15 N/25mm	7 N/25mm
	after 24 h	16 N/25mm	8 N/25mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)		covered side	open side
	at 23°C	2 h	5 h
	at 70°C	5 min	10 min
Shelf life**	2 years		
Application temperature	> +15°C		

* average ** in original packaging, at 20°C and 50% relative humidity

*** 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

