

## Description

This tape consists of a white, closed-cell polyethylene foam coated on both sides with a modified solvent acrylate adhesive. This modified solvent acrylate adhesive possesses a high initial adhesion, even on rough and difficult substrates.

## Carrier

Closed-cell polyethylene foam, white, 1000 micron

## Liner

Blue paper, 90 g/m<sup>2</sup>, both sides coated with silicone

## Adhesive

Modified solvent acrylate

## Area of use

For the installation of spray cast and extruded plastic parts such as panels, bars and ducts, as well as plexiglass mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, signs, handles and dispensers. Ideal for use in exhibition and conference fit-outs.

## Technical data

<b>Thickness*</b> (foam + adhesive)	1100 micron
<b>Density*</b>	67 kg/m <sup>3</sup>
<b>Temperature resistance***</b>	-40°C to +80°C
<b>LoopTack*</b> (FINAT TM 9)	28 N/25mm
<b>Adhesive power*</b> (FINAT TM 1, stainless steel, one side covered with 50 micron polyester film)	after 1 min 18 N/25mm after 20 min > 18 N/25mm, foam tear after 24 h > 18 N/25mm, foam tear
<b>Shear strength*</b> (FINAT TM 8, stainless steel, one side covered with 50 micron polyester film)	> 300 h at 23°C > 6 h at 70°C
<b>Temperature resistance*</b> (S.A.F.T.)	85°C
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> 15°C

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.