

# ORATAPE

## MT 95 Application Tape

Technical Data Sheet

2009/07

### Description

Transparent, polyethylene-based mounting film with a fine-pocked finish for the transfer of die-cut and computer-cut letters and symbols.

### Adhesive

Modified polyacrylate, medium adhesive strength.

### Area of use

The special composition of the polyacrylate adhesive enables unproblematic transfer of die-cut and computer-cut letters and symbols. Even after more than six month of application, a residueless removal without any considerable increase in adhesive strength has been proven. The high tensile strength of the film ensures precise positioning. This mounting film is suitable for almost all well known types of glossy or matt-finished films.

### Technical data

---

<b>Thickness*</b> (film with adhesive)	155 micron
--	------------

---

<b>Weight*</b> (film with adhesive)	110 g/m <sup>2</sup>
-------------------------------------	----------------------

---

<b>Adhesive power*</b> (FINAT TM 1, after 20min, stainless steel)	2 N/25 mm
--	-----------

---

<b>Tensile strength</b> (DIN EN ISO 527)	
along	min. 25 MPa
across	min. 25 MPa

---

<b>Elongation at break</b> (DIN EN ISO 527)	
along	min. 500%
across	min. 700%

---

<b>Shelf life**</b>	2 years
---------------------	---------

---

<b>Application temperature</b>	> +10°C
--------------------------------	---------

---

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH - Orafolstraße 2 - D 16515 Oranienburg  
Telefon: +49 (0) 33 01/864 0 - Telefax: +49 (0) 33 01/864 100  
E-Mail: verkauf@orafol.de - Internet: <http://www.orafol.d>