

LT 95

Application Tape

Description

Transparent, polyethylene-based mounting film with a fine-pocked finish for the transfer of die-cut and computer-cut letters and symbols.

Adhesive

Modified polyacrylate, low adhesive strength.

Area of use

This mounting film has been developed for special uses which requires an extraordinary low adhesive power.

Technical Data

Thickness* (film with adhesive)	150 micron
Weight* (film with adhesive)	105 g/m ²
Adhesive power* (FINAT TM 1, after 20 min, stainless steel)	<1 N/25 mm
Tensile strength (DIN EN ISO 527)	along: min. 25 MPa across: min. 25 MPa
Elongation at break (DIN EN ISO 527)	along: min. 500% across: min. 700%
Shelf life**	2 years
Application temperature	> +10°C

* average

** in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH – Orafolstraße 2 – D 16515 Oranienburg

Phone: +49(0)3301/8640 – Fax: +49(0)3301/864100

Email: graphic.products@orafol.de – Internet: www.orafol.com