



## TexWalk - Product Data Sheet

### Description

TexWalk is a revolutionary new floor media suitable for a wide range of flooring surfaces indoors & outdoors. Indoors suitable for low pile carpet, lino, timber etc. Outdoors suitable for smooth tiles and smooth concrete etc. TexWalk has a built-in textured non slip surface and does not require an overlamine. No overlamine means it's considerably faster to market plus colours are significantly brighter. Comes with a whopping R11 non slip certification (CSIRO).

### Features

- > Suitable for multiple indoor/outdoor surfaces
- > Suitable for low pile carpet
- > CSIRO approved non slip surface
- > Brilliant print quality
- > No over lamination required
- > Fast through production & fast to market. High volume / fast turn around friendly
- > Zero residue left behind when removed

Multiple indoor  
outdoor / surfaces

Suitable for  
low pile carpet

Fast production  
turn around

### Applications

- > Retail
- > Shopping centres
- > Exhibitions
- > Office
- > Car Parks
- > Footpaths
- > Concrete walls / columns

Retail

Exhibitions

Car parks

### Surfaces

#### Indoor

- > Low pile carpet
- > Lino
- > Vinyl
- > Timber
- > Tiles

Indoor

Outdoor

#### Outdoor on smooth surfaces only

- > Tiles
- > Concrete
- > Porous stone like blue stone

### Test First

If considering alternative surfaces we recommend trialling with a small piece first in a inconspicuous location. Trial over a minimum 4 week period to determine suitability for the intended surface



## Printing Methods

- > UV curable
- > Solvent
- > Eco solvent
- > Latex



## Durability

TexWalk durability depends on the surfaces it is applied to combines with the type and volume of traffic travelling over it. For high traffic areas we recommend a maximum 3 months and for low traffic areas we recommend a maximum 6 months



## Slip Resistance

Australian / New Zealand standards 4586:2004 approved. CSIRO tested R11 rating



## Storage

Shelf life is 12 months. Store in cool conditions (15-24 degrees C - humidity 40-60% rh)

## Warranty

Since there is no control under which conditions the product has been applied or has been used, all product warranty automatically end as soon as the product has been applied to any surface

## Technical Information

Size Width: 1.22m  
Length: 25.00m  
Foil Fabric with a textured matte vinyl coating (white)  
0.10 - 0.25 mm  
Adhesive acrylic solvent  
Adhesion 80µ +/- 5µ  
Total weight 385 g/m<sup>2</sup>  
Slip-resistance DIN51130 / BGR 181 R11  
Minimum application temperature +10°C / +50°F

