

Description

Ultra clear, glossy Premium Cast PVC film and the highest level of UV protection.

Release Paper

Polyester film, siliconised on one side, 75 micron

Adhesive

Solvent polyacrylate, permanent

Area of use

For the protection of digitally printed large format images in indoor and outdoor applications. ORAGUARD® 252F is recommended in combination with ORAJET® 3952F.

Technical Data

Thickness⁽¹⁾ (without protective paper and adhesive)	50 micron
Dimensional stability⁽¹⁾ (FINAT TM 14)	Adhered to steel shrinkage max. 0,1 mm
Temperature resistance⁽²⁾	Adhered to aluminium, -30° C to +70° C, no variation
Adhesive power⁽¹⁾ (FINAT TM 1, after 24h, stainless steel)	12 N/25 mm
Tensile strength⁽¹⁾ (DIN EN ISO 527)	Along: > 19 MPa Across: > 19 MPa
Elongation at break⁽¹⁾ (DIN EN ISO 527)	Along: > 120% Across: > 120%
Shelf life⁽³⁾	2 years
Application temperature	> +8° C
Maximum service life by specialist application and proper care and usage	8 years
Under vertical outdoor exposure ⁽⁴⁾	

⁽¹⁾ average ⁽²⁾ short-time exposure ⁽³⁾ in original packaging, at 20°C and 50% relative humidity ⁽⁴⁾ normal climate of Central Europe

Note

Due to the diversity of prints and printing techniques, the user should test the suitability of ORAGUARD® laminating films for the specific print purpose, prior to use. Furthermore, the application information published by ORAFOL must be followed. The batch traceability according to ISO 9001 is done on the base of the roll number.

IMPORTANT NOTICE

All ORAGUARD® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAGUARD® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAGUARD® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice. ORAGUARD® is a registered trademark of ORAFOL Europe GmbH.