ORACAL® DX01 Decorative Window Films

Description

ORACAL® DX01 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

Vertical white stripes, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life **	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average ** in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE



ORACAL® DX02 Decorative Window Films

Description

ORACAL® DX02 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

White grids, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life **	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average ** in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE



ORACAL® DX03 Decorative Window Films

Description

ORACAL® DX03 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

White circles of 3mm diameter, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life **	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average ** in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE



ORACAL® DX04 Decorative Window Films

Description

ORACAL® DX04 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

Gradient white circles, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life **	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average ** in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE



ORACAL® DX05 Decorative Window Films

Description

ORACAL® DX05 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

Gradient dots in vertical columns, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life **	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average ** in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE



ORACAL® DX06 Decorative Window Films

Description

ORACAL® DX06 is a window film series produced for interior design. It has 50 micron thickness. Interior design window films are developed as an affordable solution for creating decorative areas and privacy.

Pattern

White and grey quadrilaterals with diamond appearance, decorative window film

Release Paper

Silicone-coated transparent polyester on one side

Adhesive

Acrylic copolymer, transparent

Area of Use

The areas of use of ORAFOL decorative window films are quite extensive. Use in areas such as glass doors, showcases, room dividers, glass surfaces in meeting rooms and airport waiting rooms is recommended. They are also suitable for areas where you may need them for privacy, such as bank windows, laboratory or hospital windows.

Technical Data

Thickness*	50 micron
Film material	PET
Base material	Polyester
Adhesive power*	4 N
Shelf life**	2 years
Application temperature	>+5°C
Expected service life	5 years

^{*}average **in original packaging, at 20° C and 50% relative humidity

Note

Published information concerning ORACAL® products is based upon our knowledge and practical experience. Shared information does not give any guarantee of the quality or characteristics of the material. This document does not constitute a guarantee of any particular quality, feature and/or service life of ORAFOL products.

You can contact ORAFOL Turkey for assistance with application, disassembly, maintenance and use of ORAFOL films. If the manufacturer's instructions are not complied with, the expected service life of the products will be shortened according to our experience. ORAFOL makes no warranty and accepts no liability in applications that are outside the instructions for use and maintenance. Contact ORAFOL Turkey to reach application professionals.

IMPORTANT NOTICE

