CAD-COLOR® SUBLISTOP

DIGITALPRESSUREFOLIE, SPECIALLY FOR SUBLIMATION-DYED POLYESTER TEXTILES

Digital printable and plottable white polyurethane film, specially developed for printing on sublimation-dyed polyester textiles. It has a barrier layer that prevents the sublimation dyes from penetrating your motif.

OEKO TEX® STANDARD 100

AVAILABLE IN

- 50 cm x 25 m roll

CARE INSTRUCTIONS

Washable up to 40 degrees. Please check the washability of the fabric. Suitable for tumble drying on a gentle cycle. Not suitable for dry cleaning. Wash and iron inside out. We strongly advise against using liquid detergent, bleach, fabric softener, and laundry pods due to the aggressive ingredients that attack the film.

RECOMMENDED FABRICS

* Test before application!

- 100% Sublimation-dyed polyester*
- 100% Polyester-Cotton blends
- Softshell*

CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. Cutting too deep will cause difficulties when weeding or pressing.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

APPLICATION INSTRUCTIONS

Temperature:	140° C
Time:	10 sec.
Pressure:	Medium (#4-6 with Hotronix®)
Carrier:	Hot-warm peel

ACCESSORIES RECOMMENDED

- CAD-COLOR® MagicMask® High Tack
- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers
- Squeegee

Easy weed
Ironable
Ironable only inside out
Washable up to
Sublimation blocking
Stretchable
Flock
Thin
Sticky carrier
Multi-color application
Peel hot
Application
Pressure