



SummaCut FX Series™

D140RLFX
Performance vinyl
and contour cutter

Optimized Media Formats



- Similar to the SummaCut D60FX, the SummaCut D140RLFX has no wide grit roller. The SummaCut D140RLFX has 6 small grit rollers that are optimally placed so that most common media formats can be handled with ease.

Working Area	Target Media Width		Margin
	Inch	mm	
1324 mm	54"	1,372 mm	24 mm
1174 mm	48"	1,219 mm	23 mm
954 mm	40"	1,016 mm	31 mm
		1,000 mm	23 mm
864 mm	36"	914 mm	25 mm
720 mm	30"	762 mm	21 mm
570 mm	24"	610 mm	20 mm
454 mm	20"	508 mm	27 mm
		500 mm	23 mm
350 mm	16"	406 mm	28 mm
304 mm			
260 mm	11"	279 mm	10 mm
		297 mm	19 mm
84 mm	Scrap		



Extended Mode



- By default all Summa Cutting plotters are scanning the position of the pinch roller blocks and set the working area nicely inside the outer two pinch rollers.
- All current models have the extended load functionality. Using the extended load the boundaries (left and right) can be changed. This way the working area can be set independent of the pinch roller positions.
 - SummaCut D140RLFX has optimized media positions for most common sized material. The extended mode ensures that also other formats can be handled with minimal margin loss.
- When using OPOS, the devices automatically switch to extended mode. This way no extra handling is required for the operator.
 - SummaCut D140RLFX target market is to be bundled with a 137cm printer in a price attractive Print & Cut package. The limitations of the FX concept are minimal for this application.

Note: Working outside the standard working area has restrictions (especially when using FlexCut)



Performance



- The dual servo motor in the standard D140 has been replaced by a single servo motor.
- The maximum Speed and acceleration values remain the same (800mm/sec & 2G). However the SummaCut D140RLF will reduce its speed and acceleration quicker when it measures heavy or wide vinyl.
- Equipped with a LAN connection.



SummaCut FX Series - D140RLF
©Copyright 2018 Summa nv



Configuration



- The SummaCut D140RLFX is shipped with a stand (NO Basket)
- The SummaCut D140RLFX has 3 pinch rollers (2 outer ones (full pressure) – and 1 middle (low pressure))
 - PS the standard D140 has 4 pinch rollers.
- The SummaCut D140RLFX has the same functionality (including OPOS X, OPOS Barcode, FlexCut, LAN connection...) as a standard Summa Roll Cutter.
- Packaging is the same as the one of a standard SummaCut D140.



Pricing & Availability



- European Recommended List Price
 - 3.990,00 Euro/ex-works Summa Gistel



SummaCut FX Series - D140RLFX
©Copyright 2018 Summa nv

